

## Información técnica de hojas



**UPM**  
UPM RAFLATAC PRODUCTS  
TECHNICAL INFORMATION

4.1.2006 ENG 932

**SELF- ADHESIVE** SHEETS  
**FACE** RAFLAMATT/SHEETS  
**COATED PAPER** SH (sales code)

**Product** White, matt, machine coated, woodfree label paper.

**Use** For high quality labels with multi-colour printing.

### Typical technical values

<b>Substance</b>	80	g/m <sup>2</sup>	ISO 536	
<b>Caliper</b>	74	µm	ISO 534	
<b>Tensile strength MD</b>	5,0	kN/m	ISO 1924/1	
<b>Tensile strength CD</b>	2,0	kN/m	ISO 1924/1	
<b>Brightness</b>	97	%	ISO 2470/1	
<b>Roughness</b>	3,0	microns	ISO 8791	PPS 10
<b>Opacity</b>	93	%	ISO 2471	
<b>Gloss</b>	20	%	Hunter 75°	
<b>Printability</b>	Offset, flexography, letterpress.			

## UPM RAFLATAC

### Warranty

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot take responsibility for any damage caused through their use.

This technical sheet replaces all previous versions. All information is subject to change without notice.